



* Jaw Crusher (Crusher)
Dimension: 900x650 mm Primer type
Engine power: 75-90 Kw
Adjustable mechanism and jaw crusher can be easily adjusted.
* Main Conveyor Belt System 800 mm
Pallet type conveyor is rubber.

* Vibrating Screen System High Capacity Type
Dimension: 1600x5000mm
Engine Power 15 KW
Number Of Floors: 3 Floors

* Secondary Impact Crusher (Hard Crusher)
1120x1000 mm Special type Impact Crusher system
Engine: 132-160 Kw

* Under-Screen Stock Conveyor 1000 mm
Folding type

* Stock Conveyor 2 units 600 mm Folding type
* 2. Crusher Main Belt Conveyor 5000 mm Folding type
* Mobile Chassis System 3-Axis Special Constructed Chassis
* Hydraulic System

There are 6 hydraulic foot mechanisms in the system,
after these feet are locked, they are strengthened with 6 Fixed feet.

Hydraulic Power System 125 Liter

Magnetic Conveyor Belt 750 mm (Optional)

* Clipboard Material is Schneider Electric or Telemecanique Mark.

* Board System has Abb Soft Starter system and special control system.

All functions can be controlled with Remote Control (Radio Control System).

Generator System Optional, 6 Cylindrical diesel engine and Marelli Alternator of Cummins,
Perkins, Doosan, Deutz brands.

Capacity: Material to be Shredded and Feeding,

Variable according to the final product sizes, Capacity is 160 - 240 tons.

Dust Removal System, dust is prevented by spraying high pressure water nozzle to suppress dust in conveyors.

Feeders are Vibromotor Emtas or Italtibras, Oli Brand.

Drive Drums are Rubber Coated and Threaded.

Electric Motors are Gamak, Emtaş, Inter Mark.

Gearboxes are special gearboxes with 3 gears.

Conveyor Belt Tires Derby or Eksaş Brand.

Bearings: SKF or Equivalent Bearings

The flat product used is Ereğli Iron and Steel Product and it is A1 Size.

* By-pass system (optional)

* Magnetic magnet (optional)

* Generator System (optional)

* Additional Hopper to feed with truck (optional)

* Dust Removal System (optional)

* Frequency Control System is used instead of Soft Starter.

Approximate fuel consumption 30 - 35 Lt / hour (Optional)

** Shipping Dimensions: Width 3000 mm x Length 15.000 mm x Height 4500 mm

** All our products are European Union CE certified.

